

www.kbm.dk



RECYCLING

MINI "IN-A-BOX"



EPP beads
ready to be
recycled.



EPS beads
ready to be
recycled

HOPPER OPENING:
900X600 MM

EPS / EPP / EPE / ARCEL / NEOPOR



KBM APS
DK 3400 HILLERØD
TLF.+45 4826 8090
Homepage: www.kbm.dk

VØLUNDSVEJ 13
DENMARK
FAX.+45 4826 8016
e-mail: kbm@kbm.dk



- **If you need** to treat EPS/EPP/EPE/ARCEL pieces so they can be recycled in a production.
- **The only system on the market**, where you have a pre-crusher/granulator, a dust separation unit, a cyclone venting and a dust compactor **built into one unit**.
- To recycle by replacing new raw material is the **best economical way**, because you gain up to 80-90% of the original value of the raw material.
- **High rates of reusability**. With shape material 10-20% can normally be reused without any problems.(even more when using a KBM Styromix) and 20-50% or even 100% by block - depending on the equipment available to mould.
- Whole pieces are precrushed and granulated into individual beads, the dust is separated, the beads are conveyed to a storage silo and the extracted dust is compacted. **ALL IN ONE BOX !**
- Makes **individual beads** with very little dust generated (which is removed) and the final product can be used to mix into a production again to replace beads of new raw material.
- **Very easy installation**. Only connect the power and the ducting to the storage silo.
- Can **easily be moved around** by a forklift or similar.
- The outer parts can be taken off in a very short time and the recycling box can now be put on a truck or **into a standard container** for easy transportation where it fits in.
- Due to the **unique KBM design of the granulator** only 5-7% EPS dust is generated by granulating to individual beads.
- The very efficient dust separation ensures that there is **no production stops** afterwards due to problems with blocked core vents.
- Unique **low-maintenance cyclone venting** system which ensures that you have sufficient venting for a good dust separation without a lot of venting bags to clean.

Technical Data:

Capacity/hour EPS:

(Granulated and dust extracted EPS)

Sieve with 6 mm holes (shape): 6-8 m³ (210-280 ft³)

Sieve with 10 mm holes (block): 9-10 m³ (315-350ft³)

Sieve with 12 mm holes (block): 12-13 m³ (420-455 ft³)

Capacity/hour EPP:

(Granulated and dust extracted EPP)

Sieve with 6 mm holes (EPP): 60-100kg (27-220 lbs)

Sieve surface:

0.9 m² (9.7ft²)

Space required

approx. 6 m² (65 Ft²)

Measurements:

L x W x H

Fully mounted: 2.23x2.73x3.56 m (88x108x140")

Dismounted for transport: 2.23x2.23x2.22 m (88x88x87")

Storage silo (6): 2.0x2.0x6.0 m (80x80x240")

(Any size available)

Size Silo bag: 2.0x2.0x4.0 m (80x80x160")

(Any size available)

(approx. 17 m³/600 ft³)

Pipe connections:

160 mm (6")

Hopper opening:

900x600mm (36x24")

Reuseable EPS material after recycling:

min. 93-95 %

Extracted EPS dust and fines:

max. 5-7 %

Dust content after dust separation:

max. 1 %

(Experienced by EPS granulated on a KBM granulator.)

Electrical load:

EPS

EPP

Recycling "in-a-box"

18.4 Kw 31.9 Kw

Voltage: 3x400V/50Hz, 3x480V/60Hz or other voltages.

How to reuse in practice:

Use the KBM Styromix mixing unit to make a very accurate mixing directly on the moulding machine. Increases the mixed ratio possible by avoiding demixing of new and recycled material and is very easy to operate.

SUBJECT TO ALTERATIONS

