


www.kbm.dk



STYROMIX / STYROMETER MIXING SYSTEMS

EPS / EPP / EPE / ARCEL / NEOPOR


FOR SHAPE MOULDING MACHINES



STYROMIX
MIXING for EPS and EPP etc.

NEW STYROMIX 3 SYSTEM !!!

FOR BLOCK MOULDS OR
FOR PRE-PRESSURIZING TANKS



STYROMETER
MIXING for EPS and EPP etc.



KBM APS
DK 3400 HILLERØD
TLF.+45 4826 8090
Homepage: www.kbm.dk

VØLUNDSVEJ 13
DENMARK
FAX.+45 4826 8016
e-mail: kbm@kbm.dk



STYROMIX (for the shape moulders):

The KBM STYROMIX System is designed to obtain a more accurate metering and mixing of recycled EPS or EPP materials to the new EPS or EPP beads. It can be mounted directly before each individual moulding machine (mounted on or close to each machine - or mounted near the silos).

The STYROMIX System starts mixing whenever there is vacuum from a moulding machine.

The STYROMIX System is suitable for EPS or EPP granulated and dust extracted material and since the mixing takes place directly before the material reach the hopper on the moulding machines, the de-mixing of the mixture is minimized or even eliminated compared to mixing after the pre-expander.

The ratio of the recycled material to the new beads is from 0% to 99% in steps of 1%.

The STYROMIX 3 system has only one control panel for every 3 mixing units and is very easy to use.

The vacuum used to suck the material from the storage silos to the moulding machines, is to be provided from the customers existing vacuum system.

It is very simple to operate all systems from the control panels.

STYROMIX UNIT:	
Throughput per unit:	100 L/Min
Compressed air:	5 Bar
Hose connections (hose i.d.):	40 mm (1,5") or 50 mm (2")
Dimensions (each unit):	
Length:	435 mm (17")
Width:	390 mm (16")
Height:	680 mm (27")
Electrical load STYROMIX 3:	30 VA

STYROMETER (for the EPS block moulders or for EPP mixing before the pre-pressurizing tank):

The KBM STYROMETER System is designed to meter and mix the recycled and new material together right before the block mould to minimize de-mixing.

Each silo contains one material e.g. recycled and virgin material. The speed of the cell-wheels (airlocks) is steplessly adjustable from 5% to 95% with **one mutual potentiometer** to set the required mixing ratio. It is also possible to program a number of pre-set ratios (5%, 10%, 15%, etc.) to simplify the settings.

The cell-wheel (airlock) principle ensures an accurate mixing/metering independently of the pressure in the silos when they are being refilled by a blower. This is a problem by the screw-feeding systems.

The system can also be delivered for existing silos.

STYROMETER	MINI	MAXI	JUMBO	GIGANT
Capacity (m3/h):	30	100	180	300
(CuFt/h):	1,000	3,333	6,000	10,000
MORE CAPACITY ON REQUEST.				
Height m:	6,0	6,0	6,0	6,0
Width m:	2,0	3,0	4,0	5,0
Length m:	2,0	3,0	4,0	5,0
Electrical load:	Up to 3 KW			

SUBJECT TO ALTERATIONS

2019/09 - 2019/09 R14E

